

DDC2B Firmware upgradable OS Support:Windows 2000, Windows XP, Windows Vista, LINUX, Mac, Sun and FreeBSD SUN/Mac keyboard support and emulation**1.PC keyboard combinations emulate SUN/Mac keyboards.*2.SUN/Mac keyboards only work with their own computers , Package Content , 1x USB KVMP Switch 2x USB KVM Cables 1x Firmware Upgrade Cable 1x User Manual 1x Quick Start Guide , Diagram ,+ View enlargement , Specification ,Computer Connections 2 Port Selection Hotkeys, Pushbutton USB Port/Audio Port Selection Hotkey Connectors Console Ports Keyboard 1 x USB Type A Female (White) Video 1 x HDB-15 Female (Black) Mouse 1 x USB Type A Female (White) Speaker 1 x Mini Stereo Jack Female(Green) Microphone 1 x Mini Stereo Jack Female (Pink) KVM Ports Keyboard/Video/Mouse 2 x SPHD-15 Female (Yellow) Speaker 2 x Mini Stereo Jack Female (Green) Microphone 2 x Mini Stereo Jack Female (Pink) USB Hub 2 x USB Type A Female (Black) F/W Upgrade 1 x RJ11 Female (Black) Power 1 x DC Jack Switches Port 2 x Pushbutton F/W Upgrade 1 x Slide LEDs On Line/ Selected 2 (Orange) USB Link 2 (Green) Emulation Keyboard/Mouse USB Video 2048 x1536, DDC2B Scan Interval 1~99 seconds Power Consumption DC5V, 1.2W Environment Operating Temp. 0~50°C Storage Temp. -20~60°C Humidity 0~80% RH, Non-densing Physical Properties Housing Metal Weight 0,49 kg Dimensions (L x W x H) 14.00 x 8.50 x 5,50 cm Technische Details:

Allgemein

Gerätetyp

KVM-Switch - 2 Anschlüsse

Gehäusetyp

Desktop

Untertyp

KVM

Ports

2 x KVM port(s)

Anz. lokale KVM-Benutzer

1 lokaler Benutzer

Tastatur-/Mausschnittstelle

USB

Max Auflösung

2048 x 1536

Leistungsmerkmale

Remote Port Selector

Erweiterung/Konnektivität

Schnittstellen

2 x Tastatur (USB) Type A | 2 x VGA HD-15 | 2 x Maus (USB) Type A | 1 x VGA HD-15 | 1 x Tastatur (USB) Type A | 1 x Maus (USB) Type A

Verschiedenes

Enthaltene Kabel

1 x Tastatur- / Maus- / Video-Kabel - 90 cm

Produktzertifizierungen

DDC-2B, RoHS, WEEE

Maße und Gewicht

Breite

7 cm

Tiefe

8,2 cm

Höhe

2,5 cm

Gewicht

310 g

Umgebungsbedingungen

Min Betriebstemperatur

0 °C

Max. Betriebstemperatur

50 °C

Zulässige Luftfeuchtigkeit im Betrieb

0 - 80% (nicht kondensierend)

Min. Lagertemperatur

-20 °C

Max. Lagertemperatur

60 °C

Weitere Bilder

